

Surface treatment

Solutions for Textile
and Synthetic Materials



Lamberti
textile printing & finishing

Designing
new values
in chemistry

A smart toolbox to face the coating's challenges!

Lamberti range provides high performance building blocks to create **innovative solutions** with reduced environmental impact for infinite applications on textile printing, textile finishing/coating and synthetic materials.

We at Lamberti foster our path towards sustainability and circular economy moving in four main directions:

- **Performances:** higher durability of goods;
- **Biobased content:** higher renewable raw materials content without decrease in performances;
- **Waterborne products:** continuous focus on the cosolvent and Volatile Organic Compound (VOC) reduction;
- **Process optimization:** constant improvement of industrial processes with the aim to reduce the consumption of energy, water and air, improving efficiency and sustainability.





Our technological expertise

**Biobased Waterborne
technologies**

**Biodegradable
surfactants**

Natural Polymers


Anionic polyurethane dispersions

| Polycarbonates | | | | | | | | | | | | |
|--|---------------|---------------|----------|-------|-----------------------|------------------------|-------------------------|--------------|---------|---------|----------|------------|
| Product | Solid content | Co-solvent | Hardness | | Mechanical properties | | | Applications | | | | |
| | | | König | Shore | 100 % modulus (MPa) | Tensile Strength (MPa) | Elongation at break (%) | Padding | Foaming | Coating | Printing | Lamination |
| ROLFLEX® K 077 | 35 % | MEK - <1% | 110 | D 55 | 15** | 26** | 250** | x | | x | | |
| ROLFLEX® ACF ● | 35 % | DMM* - 8 % | 153 | D 65 | 13** | 18** | 190** | x | x | x | | |
| ROLFLEX® T 87 | 35 % | DMM* - 4 % | 35 | - | 5.5 | 25 | 350 | | | x | | |
| Polyesters | | | | | | | | | | | | |
| ROLFLEX® VLM | 35 % | MEK - <1% | 55 | - | 9 | 42 | 405 | | | x | | |
| ROLFLEX® AL 62 | 35 % | DMM - 5 % | 47 | D 50 | 6.8 | 25 | 480 | | | x | | |
| ROLFLEX® T 63 ● | 35 % | DMM - 5 % | 27 | A 70 | 2.6 | 20 | 530 | x | | x | | x |
| ROLFLEX® BZ 78 ● | 50 % | Acetone - <1% | 28 | A 65 | 1.1 | 5.5 | 600 | x | x | x | x | |
| ROLFLEX® DAK 07 ● | 40 % | MEK - <1% | - | A 40 | 1.3 | 4 | 880 | | | x | | x |
| ROLFLEX® CZ 47/P ● | 50 % | Acetone - <1% | - | A 50 | 0.5 | 4 | 800 | | x | x | x | x |
| Polyethers | | | | | | | | | | | | |
| ROLFLEX® MV 15 ● | 30 % | DMM* - 5 % | 84 | D 60 | 12 | 20 | 240 | x | | x | | |
| ROLFLEX® MV 24  | 35 % | DMM* - 5 % | 80 | - | 8 | 15 | 300 | x | | x | | |
| ROLFLEX® D 67 ● | 40 % | FREE | 30 | - | 4.1 | 18 | 680 | | x | x | | |
| ROLFLEX® DV 5 | 35 % | DMM* - 5 % | 27 | A 80 | 4 | 17 | 650 | | | x | x | |
| ROLFLEX® ADH 190 | 35 % | FREE | - | A 70 | 3.5 | 20 | 600 | | | x | | x |
| ROLFLEX® D 27 ● | 40 % | FREE | 28 | D 30 | 3.5 | 18 | 530 | | | x | | |
| ROLFLEX® HS 18 ●  | 60 % | FREE | 38 | A 50 | 3 | 15 | 600 | | x | x | x | x |
| ROLFLEX® D 70 | 40 % | FREE | - | A 40 | 1.5 | 13 | 800 | | x | x | | |
| ROLFLEX® AD 45 ●  | 30 % | DMM* - 3 % | - | A 60 | 1.4 | 20 | 550 | x | | x | | x |
| ROLFLEX® FR 66 | 40 % | FREE | - | A 30 | 0.6 | 3 | 800 | x | x | x | | |
| ROLFLEX® A 440  | 40 % | FREE | - | A 25 | 0.3 | 1 | >1000 | | | x | | x |

Non-ionic polyurethane dispersions

| Polyesters | | | | | | | | | | | | |
|-----------------|---------------|-------------|----------|-------|-----------------------|------------------------|-------------------------|--------------|---------|---------|----------|------------|
| Product | Solid content | Co-solvent | Hardness | | Mechanical properties | | | Applications | | | | |
| | | | König | Shore | 100 % modulus (MPa) | Tensile Strength (MPa) | Elongation at break (%) | Padding | Foaming | Coating | Printing | Lamination |
| ROLFLEX® 3511 | 30 % | DMM* - 5 % | 20 | A 60 | 0.9 | 6 | 850 | x | | x | x | |
| Polyethers | | | | | | | | | | | | |
| ROLFLEX® N 58 ● | 30 % | Acetone <1% | - | - | - | - | - | x | | x | | |
| ROLFLEX® N 54 ● | 30 % | Acetone <1% | - | A 55 | 0.5 | 1 | 900 | x | | x | x | |
| ROLFLEX® SW 3 ● | 35 % | Acetone <1% | 20 | A 35 | 0.5 | 2.5 | 1000 | x | | x | | |

● Bluesign® approved product

 Available version based on renewable resources


* Dipropylene glycol Dimethyl ethe

** Film made using co-solvent

Cationic polyurethane dispersions

| Polycarbonate | | | | | | | | | | | | |
|------------------|---------------|--------------|----------|-------|-----------------------|------------------------|-------------------------|--------------|---------|---------|----------|------------|
| Product | Solid content | Co-solvent | Hardness | | Mechanical properties | | | Applications | | | | |
| | | | König | Shore | 100 % modulus (MPa) | Tensile Strength (MPa) | Elongation at break (%) | Padding | Foaming | Coating | Printing | Lamination |
| ROLFLEX® C1 | 30 % | Acetone <1 % | 25 | D 40 | 3 | 8 | 300 | x | | x | | |
| Polyethers | | | | | | | | | | | | |
| ROLFLEX® CN 29 ● | 30 % | FREE | - | - | - | - | - | x | | x | | |

Urethan-acrylic hybrid resins

| Product | Solid content | Co-solvent | Hardness | | Mechanical properties | | | Applications | | | | |
|---|---------------|--------------|----------|-------|-----------------------|------------------------|-------------------------|--------------|---------|---------|----------|------------|
| | | | König | Shore | 100 % modulus (MPa) | Tensile Strength (MPa) | Elongation at break (%) | Padding | Foaming | Coating | Printing | Lamination |
| ROLFLEX® XL23 | 35 % | Acetone <1 % | 150 | - | 18** | 25** | 145** | x | | x | | |
| ROLFLEX® PU 148 ●  | 35 % | Acetone <1 % | 108 | D 55 | 17** | 25** | 230** | x | | x | | |
| ROLFLEX® V13 | 35 % | DMM* - 4 % | 75 | D 60 | 10 | 20 | 280 | x | | x | | |
| ROLFLEX® K80 | 35 % | Acetone <1 % | 22 | D 45 | 5.5 | 13 | 350 | x | | x | | x |
| ROLFLEX® K110 ● | 40 % | Acetone <1 % | - | A 45 | 0.25 | 1.4 | >1000 | x | | x | | |

Acrylic resins

| Product | Solid content | Tg (°C) | Hardness | | Applications | | | | |
|------------------|---------------|---------|----------|--|--------------|---------|---------|----------|------------|
| | | | König | | Padding | Foaming | Coating | Printing | Lamination |
| SIPACRIL CP 34 | 45 % | -30 | - | | x | x | x | x | |
| SIPACRIL CP 29 ● | 45 % | -11 | <20 | | x | | x | x | x |
| SIPACRIL HP 1000 | 35 % | -13 | - | | x | x | x | | |
| SIPACRIL MA ● | 40 % | -10 | <20 | | x | | x | x | |
| SIPACRIL PLA | 40 % | +12 | 30 | | x | | x | | x |
| SIPACRIL KR | 47 % | +16 | 35 | | x | x | x | | |
| SIPACRIL RGD | 40 % | +29 | 56 | | x | | x | | |


Self-crosslinking

| | | | | | | | | | |
|--------------|------|-----|----|--|--|--|---|--|--|
| SIPACRIL AMC | 38 % | -3 | ? | | | | x | | |
| SIPACRIL 298 | 40 % | +23 | 38 | | | | x | | |

Hydroxylated

| | | | | | | | | | |
|--------------|------|-----|-----|--|---|---|---|--|--|
| SIPACRIL 302 | 50 % | -40 | 50 | | x | x | x | | |
| SIPACRIL OX | 40 % | +55 | 150 | | x | | x | | |

Inherently matt polyurethane dispersions

| Product | Solid content | Co-solvent | Hardness | | Chemistry | Gloss unit 60 ° |
|--|---------------|------------|----------|--|--------------------------|-----------------|
| | | | König | | | |
| ROLFLEX® OP 80  | 32 % | FREE | 36 | | Soft Polyether | <1 |
| ROLFLEX® OP 888 ● | 32 % | FREE | 48 | | Soft Polyether | 0.8 - 1.2 |
| ROLFLEX® OP 997 | 25 % | DMM* - 3 % | 80 | | Very rigid Polycarbonate | <0.6 |
| ROLFLEX® OP 99 | 28 % | DMM* - 3 % | 52 | | Rigid Polycarbonate | <1 |

The Lamberti Group

Explore, Design, Provide, Evolve.

We design and produce customized chemical solutions for different industries: not simply products or formulations, but sets of skills, capabilities, visions, developed with dedication and attention to our customers. Our science is made of experience, technology, and precision, for tailoring and delivering high performing solutions to our customers. Our ability to fit any market evolution demonstrates our capacity to be creative and innovative.

The history of our company is continually written by people's living stories.

Since 1911, our experience stems from over a century of history. From the initial affiliation

to the textile industry, we have learned the value of being part of structured eco-systems. Over time, we have invested in industrial plants and laboratories to cover all geographies. We have fostered a network of relationships, a rich wellspring of experience that gives value to our people.

We want to do better, creating a positive legacy for the future of the planet and living species.

Sustainability became a crucial challenge for Lamberti that we addressed with the subscription to international programs (RSPO and Ecovadis) as well as with the voluntary publication of the Group's Sustainability Report (2020).

The cited Company names, product names, designs, logos and other distinctive signs are registered as trademarks in many Countries, on a worldwide basis. Any unauthorized use of any IPR by any third parties will be prosecuted under applicable Laws on a Country by Country basis.

Our technologies per market

| | Cellulosics | Hydrocolloids | Acrylics | Waterbased polyurethanes | Oleochemicals |
|--------------------------------|-------------|---------------|----------|--------------------------|---------------|
| Agriculture | • | • | • | | • |
| Personal care | • | • | • | • | • |
| Food and regulated industries | • | • | | | |
| Oil&gas | • | • | • | | • |
| Mining and civil engineering | • | • | • | | • |
| Ceramics and glassware | • | • | • | • | • |
| Surfactants | | | | | • |
| Wetend paper | • | • | | | |
| Drymix for construction | • | • | | | • |
| Textile printing and finishing | • | • | • | • | • |
| Architectural paints | • | • | • | • | • |
| Coated and functional paper | • | • | • | • | • |
| Industrial coating | | | • | • | • |
| Digital inks | | | • | • | • |
| Inks ingredients | | | • | • | • |
| Leather finishing | | | • | • | |
| Synthetic materials | | • | • | • | • |

